

Waterlink Tere'o Touch

pH, Free or Active Chlorine Controllers (Optional Temperature Sensor)

The Tere'o Touch is a precise monitoring and dosing system with options for monitoring free or active chlorine and pH, with optional temperature sensor.

Remote Monitoring

- Optional communication modem for remote monitoring via Ethernet or SIM communication, providing easy access to Waterlink Remote Monitoring. Bi-directional remote access available via BMS
- USB port for data export or software update

Applications

Suitable for all domestic and commercial aquatic environments, including common pools in buildings, retirement villages, hotels, hospital pools, learn-to-swim facilities, council pools, school pools, aquatic centers, government facilities, gyms, and wellness centres.



Simplicity & Efficiency

- Intuitive touch-screen controller
- User-friendly interface with adaptable configurations for various pool volumes and actions.
- Dosing stops on high/low alarms, with programmable maximum daily dosing time
- Compatible with all chlorine types: stabilised chlorine, liquid chlorine, salt chlorination, pellets
- Versatile multi-parameter control
- Continuous self-diagnosis for optimal efficiency
- Various regulation types: PID (cycle or pulse), on/off, threshold, hysteresis

Waterlink Tere'o Touch

pH, Free or Active Chlorine Controllers (Optional Temperature Sensor)

Code	Description
	TERE'O Touch
	The Waterlink Tere'o Touch is manufactured by Syclope Electronique, a pool dosing technology leader trusted by water treatment giants like Prominent, Veolia, Suez, and more. Tere'o Touch is a precise monitoring and dosing system that provides options for monitoring free or active chlorine, pH and temperature, the Tere'o is available in three options.
TERA	Active chlorine, pH and optional temp sensor. Used for indoor pools with bromine, liquid chlorine, or salt chlorination. cyanuric acid MUST BE 0ppm or less than 2ppm.
TERF	Free chlorine, pH and optional temp sensor. Highly accurate Tolerable to cyanuric acid Levels up to 40ppm. Not good with by-products of electrolysis (salt chlorination)
	Options:
PK010	4-20mA temp sensing kit, includes 50mm PVC tee.
TVF	Tere'o colt-free adaptor (per channel) for salt chlorination, etc.
	Remote Monitoring
	Waterlink basic monitoring, hosting only. Includes 1 year of data on file, email-only alerts to an unlimited number of users. No intervention by Waterlink staff. Requires a customer-supplied internet connection or SIM card.
WLSMY	Yearly fee
WLSMM	Monthly fee
	Waterlink deluxe monitoring. Includes 2 years of data on file, email and SMS alerts to an unlimited number of users. Waterlink staff check and action alerts during business hours. Telstra SIM supplied by Waterlink.
WLDM	Monthly fee
WLMODEM	Waterlink modem. Requires a Telstra or Optus SIM, or a LAN Cable

Other Waterlink Dosing Controllers

Hydro Touch pH & ORP controllers provide the ultimate solution for high-performance precision dosing, ideal for both residential and commercial use with pools and spas up to 160,000 litres.

Hydro Touch Controller Models



CHYT0454AU: pH and ORP controller automatically controls your sanitiser and pH levels via seamless integration with your existing chlorinator and the onboard DULCOFLEX peristaltic pumps that dose diluted acid.



CHYT0444AU: pH and ORP controller automatically controls your sanitiser and pH levels via two onboard DULCOFLEX peristaltic pumps that dose your liquid sanitiser and diluted acid.

The Odi Touch is a versatile and multi-parameter monitoring and dosing System, offering up to 8 parameters for precise water analysis. It provides options for monitoring free or active chlorine, total chlorine, pH, conductivity, temperature, and more.

Odi Touch Controller Models



ODIA: Active chlorine, pH and temp sensor. Used for indoor pools with bromine, liquid chlorine, or salt chlorination.

ODIF: Free chlorine, pH and temp sensor. Highly accurate Tolerable to cyanuric acid Levels up to 40ppm. Not good with by-products of electrolysis (salt chlorination)

ODFT: Free chlorine, pH, Temp and total chlorine sensor. Highly accurate. Tolerable to cyanuric acid to 40ppm. Not good with byproducts of electrolysis (salt chlorination)

ODIFTS: Free chlorine, pH, Temp and total chlorine sensor. Highly accurate. Tolerable to cyanuric acid to 40ppm. Good with by-products of electrolysis (salt chlorination)

Waterlink Equipment Pty Ltd

Factory 2/40 Titan Drive
Carrum Downs, VIC 3201 Australia

For Further Information:

P: 1300 897 200 sales@waterlink.com

waterlink.com

Accurate as at: 13/03/2024



Proud supporter of Austswim